

UISP Console



Mechanical

| | |
|---------------------|---|
| Dimensions | 210.4 x 140.2 x 43.7 mm (8.28 x 5.52 x 1.72") |
| Weight | 1.45 kg (3.2 lb) |
| Enclosure materials | SGCC steel, polycarbonate |

Hardware

| | |
|-------------------------|---|
| Networking interface | (8) 10/100/1,000 MbE RJ45 LAN ports (1) 10/100/1,000 MbE RJ45 WAN port (1) 1/10G SFP+ LAN port (1) 1/10G SFP+ WAN port |
| Management interface | Ethernet In-Band Bluetooth |
| Processor | Quad-core ARM® Cortex®-A57 at 1.7 GHz |
| Memory | 4 GB DDR4 |
| Onboard flash storage | 16 GB eMMC |
| Onboard storage | 128 GB SSD |
| Card slot | (1) microSD |
| Power method | (1) External AC/DC adapter (1) Power TransPort DC input 27V DC, 1.5A |
| Power supply | 24V DC, 2.5A power adapter (included) |
| Supported voltage range | 24–28V DC |
| Max. power consumption | 30W |
| ESD/EMP protection | Air: ± 15kV, contact: ± 8kV |
| Operating temperature | -10 to 50° C (14 to 122° F) |
| Operating humidity | 5 to 95% non-condensing |
| Certifications | CE, FCC, IC |

LEDs

| | |
|-----------------|---------------------|
| System | Status |
| RJ45 data ports | Speed/link/activity |
| SFP+ data ports | Speed/link/activity |

